



Visit product page



KOS SUB

L006213

Line Array Kos SUB, 600watt RMS, Class D amplifier, DSP Setup, Xover design for satellite (90Hz or 120Hz), Phase switchable(0/180), Output Mode switchable(link/Xover), Active vented subwoofer, 35-120 Hz, , Max output spl(1m) 122dB, 12" subwoofer, 2.5"VC, Plywood with polyurea painted finish and grill 1.2mm steel, LED power / signal / clip indicator.

TECHNICAL DETAILS

Technical Specifications

1x XLR Input.

1x XLR Link Output.

Power output: 600 Watt RMS.

Volume control.

Power supply: 220/240 Volt AC, 50 Hz.

Class D + switching power design.

LED power / signal / clip indicator.

Xover design for satellite (90 Hz or 120 Hz).

Phase switchable (0/180), output mode switchable (link/Xover).

Active vented subwoofer.

Frequency Response: 35/120 kHz.

Impedance: 8 Ohm.

Max. Output SPL (1m): 122 dB.

12" Woofer, 2.5 VC.

Plywood cabinet with polyurea painted finish.

1.2 mm steel grill mesh.

Package: 62,5 x 53 x 61 cm, 1 set / 27Kg.

Packing Details

Carton: 59x59x55 - 30 kg

PHOTOS

