



Visit product page



NAXOS 18A SUB

L005681

Professional plywood active vented subwoofer 18 inch with DSP, 18" woofer, 3" VC 85ohm, 500w RMS, D class amplifier, 133 dB Spl, Crossover design for satellite.

TECHNICAL DETAILS

Technical Specifications

Amplifier:

German Engineering Class D amplifier + switching power supply

Inputs: 2x XLR / TRS Line.

Outputs: 2x XLR Line.

Power output: 500 Watt RMS @ 8 Ohms / 1500 Watts Peak.

Main volume control.

Power input: 100/240 Volt AC, 50/60 Hz switchable.

Switchable phase (0/180°)

LED indicator: Power, signal, clip.

Speaker:

Active vented subwoofer.

Frequency response: 35 - 150 Hz.

Max output SPL: 133 dB.

Impedance: 8 Ohm.

18" subwoofer, 3" VC 85 oZ.

Plywood cabin with black painted finish.

1,5mm steel mesh.

35mm stand pole.

Rubber cover on the edges.

Dimensions: 74 x 63,5 x 76,5 cm.

Net weight: 44 Kg.

Packing Dimensions

Dimensions: 74 x 64 x 77 cm

Weight: 64 Kg.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



iCover Naxos 18 Sub
Cover for Naxos18 Sub



IHOS Wheels Kit
Set of 4 swivel wheels kit
with brake for IHOS Sub

