



Visit product page



TILOS SYSTEM I

L006023

Tilos System I configuration that can cover 200 people,
Professional plywood active vented subwoofer 2 X10 inch and 1 pc
Aluminium full range column speakers for the Tilos system,

TECHNICAL DETAILS

TILOS C

Passive full range column speaker.

Directivity: 90° H x 10° V.

Maximum output SPL: 120 dB.

Frequency response: 200 - 20 kHz.

Impedance: 8 Ohms.

200 Watt RMS.

Driver: 12x 2,75" full range line array.

Aluminium cabinet, 1 mm steel mesh.

Dimensions: 104 x 24 x 22 cm.

Weight: 7 Kg.

TILOS L

Active vented subwoofer.

Inputs: XLR/TRS combo jack.

Output: XLR balanced line, XLR LINK, SAT Out.

250 Watt RMS (subwoofer) & 250 Watt RMS (satelite).

Subwoofer volume control, +4 / -10 dB sensitivity switch.

Power Input: 115 / 230 Volt AC, 50 / 60 Hz switchable.

German Engineering Class D amplifier + switching power supply.

Sat Mode selection.
Power / clip indicator.
DSP effect processor.
Excellent compressor.
Frequency response: 50 - 200 Hz.
Max. output SPL: 118 dB.
Driver: 10" subwoofer, 2,5" VC 45 oZ.
PLY cabinet with black painted finish.
1,2 mm steel mesh.
Dimensions: 56,5 x 40 x 60,5 cm.
Weight: 16,5 Kg.

PHOTOS



PRODUCT VIDEO



