



Visit product page



## IPA-360

L005752

Public Address mixer amplifier 360w, 6 zones speakers with volume control, 100V / 70V constant voltage output, 8 ohm constant resistance output, mp3, bluetooth, FM tuner, USB interface, LCD screen, 2 line input, 3 mic input, 1 line output. Treble and Bass,

### TECHNICAL DETAILS

#### Features

- 6 zones speaker output with individual volume control.
- Built-in MP3 player, support Mp3, WMA and WAV format, USB flash disk input port.
- Built-in FM tuner.
- With Bluetooth playback function, can connect the mobile phone Bluetooth and play the music in the mobile phone.
- Built-in Chime and Siren.
- 2 Aux, 3 Mic input and 1 Aux output.
- Mic 1 input has priority (Mute other audio input).
- Power, Signal and Clip LED indicator.
- Volume control for each input and master output volume control.
- Treble and bass control.
- 1 00V high impedance output and 8ohms low impedance output.
- 128\*64 LCD display for MP3 and FM tuner operation.
- 4 repeat mode for MP3 player: random, repeat one, repeat all in a file and repeat all.
- LCD display can display name of music, playing time and remain time.
- With dynamic spectrum display, more dynamic design.
- Perfect power amplifier protection mechanism.

#### Technical Specifications

- Rated power: 360W
- Mic input: -60dB, 6000, unbalanced, 6.3mm TS port

AUX input: -20dB, 31 0kΩ, unbalanced, Stereo RCA port

Aux output: 0dB, 6000, unbalanced, Stereo RCA port

Speaker output: High Impedance: 1 00V, 70V; Low Impedance: 80.

Volume control for each zone: 6 zones speaker output with individual volume control. Note: the power capacity for each zone can reach the rated power of amplifier. But make sure that the total power of zone 1 ~6 can not exceed the rated power.

Protection: AC fuse, overheating, overvoltage, overcurrent, short, DC, and muting during power on protections.

EQ for Master output: Treble:± 12dB at 10kHz; Bass:± 9: 12dB at 100Hz

Frequency response: 20~20kHz (±3dB).

S/N: Microphone input >66dB; AUX input >75dB

THD: <0.5% at 1 kHz at 1/3 rated power.

Power input: 220~240VAC, 50/60Hz.

Power consumption: 350 Watt at rated power.

Temperature / humidity operation conditions: -10°C ~ +40°C, <95%.

Dimensions: 482 x 88 x 350 mm (W x H x D).

Shipping weight: 14 Kg.

Shipping dimensions: 0.0382CBM, 58(W) x 47(H) x 14(D) cm.

## PHOTOS



## PRODUCT VIDEO



