



Visit product page



CLIMATE HORN

L006066

Outdoor IP66 Horn Speaker, Built-in 70V/100V transformer, built-in LF 6.5" and 1" HF driver, ABS plastic and steel grille. Frequency Response 90Hz-20kHz, 362x252x310mm , 4kg.

TECHNICAL DETAILS

Specifications

Model No: CLIMATE HORN

Rated Input 50W@100/70V; 100W@8Û

Max Input 75W@100V; 150W@8Û

High Impedance 200Û, 400Û, 800Û, 1.1kÛ, 2.2kÛ, 2.8kÛ

Power Taps 100V: 50W, 25W, 12.5W, 9W, 4.5W, 3.5W

70V: 25W, 12.5W, 6.25W, 4.5W, 2.25W, 1.75W

SPL (1W /1m) 99dB

MAX SPL (Rated /1m) 116dB@100/70V; 119dB@8Û

Frequency Response(-10dB) 90Hz~20kHz

Dispersion (4kHz / 1kHz) 30° / 65°

Power selecting Way

Various combinations: 100V: red and yellow: 50W;

yellow and green: 25W; green and white: 12.5W;

red and green: 9W; yellow and white: 4.5W;

red and white: 3.5W; red and black: 8Û

Material Housing: High Impact ABS; Grille: Steel

Color Grey

Temperature / Humidity -30°C~60°C; <95%

Water Protection IEC529 IP66

Speaker Component 6.5"woofer + 1" tweeter

Dimensions 362(W) x 252(H) x 310(D) mm

Weight 3.9kg

Mounting U Type Mounting Bracket

Shipping Weight 5kg, 1pc

Shipping Dimensions 0.0437CBM, 39 x 28 x40 cm, 1pc

PHOTOS

